IN THE CLAIMS

Please amend the claims as follows:

- (original) A method for selecting a signal from a plurality of signals received by a component in an AV system comprising:
- adding (106) an identifier to a signal in dependence on the signal being generated by an active first component;
- sending (108) the signal from the active first component;
- receiving (110) a plurality of signals at a second component;
- for each signal of the plurality of received signals:
 - o analysing (112) the signal for the presence of the identifier; and
 - o where the identifier is present determining (116) and storing at least one parameter associated with the identifier;

and

- selecting (124) a signal from the plurality of received signals in dependence on stored ones of the parameters.
- 2. (original) A method as claimed in claim 1 wherein the identifier comprises at least one frequency component in the range 20kHz to 500kHz.

- (original) A method as claimed in claim 2 wherein the identifier comprises a frequency component of 22kHz.
- 4. (currently amended) A method as claimed in any of claims 1 to 3claim 1 wherein the at least one parameter comprises a value related to the time of commencement of the first component becoming active and where the signal is selected based on the most recent time of commencement.
- 5. (currently amended) A method as claimed in any preceding $\frac{1}{2}$ elaimclaim 1 further comprising, prior to the step of receiving, the step:
- communicating (109) to other components of the system a relevant parameter associated with the identifier;
 prior to the step of selecting, the step:
- acquiring (123) the relevant parameter at the second component; and

wherein the step of selecting a signal from the plurality of received signals is on the basis of a comparison of stored ones of the parameters and the relevant parameter.

- 6. (original) A method as claimed in claim 5 wherein the at least one parameter comprises a component address.
- 7. (original) A method as claimed in claim 6 wherein the relevant parameter comprises the component address of the active first component.
- 8. (currently amended) A method as claimed in claim 6 or 7 wherein the component addresses conform to the Project50 standard.
- 9. (original) An AV system comprising at least a first component (202, 204) connected to a second component (206) by a connection means, wherein the first component is operable to:
- add an identifier to a signal in dependence on the first component being active;
- send the signal to the second component;
 and wherein the second component is operable to:
- receive from at least one first component a plurality of signals;
- for each signal of the plurality of received signals:
 - o analyse the signal for the presence of the identifier; and
 - o where the identifier is present determine and store at least one parameter associated with the identifier;

and

- select a signal from the plurality of received signals in dependence on stored ones of the parameters.
- 10. (original) An AV system as claimed in claim 9, wherein the first component is further operable to:
- communicate to other components of the system a relevant parameter associated with the identifier;
 and wherein the second component is operable to:
- acquire the relevant parameter at the second component; and wherein the step of selecting a signal from the plurality of received signals is on the basis of a comparison of stored ones of the parameters and the relevant parameter.
- 11. (currently amended) A system as claimed in claim 9—os 10, wherein the connection means supports the sending of analogue AV signals.
- 12. (original) A system as claimed in claim 11, wherein analogue AV signals comprise analogue audio via phono connector.

- 13. (currently amended) A system as claimed in any of claims $\frac{10 \text{ to } 12\text{claim }10}{10}$, wherein the connection means comprises a bus (350) to support the communication of the relevant parameter.
- 14. (currently amended) A system as claimed in claim 13, wherein the bus is Scart/HDMI supporting Project50/CEC protocols.
- 15. (currently amended) A system as claimed in claim 13—er 14, wherein the identifier is communicated using the user data bits of the SP/DIF protocol.
- 16. (currently amended) A first component (400) for use in the system of any of claims 9 to $15 \frac{1}{100} = 15 \frac{1}{100} = 15$
- a user interface (402) operable to receive user commands;
- a source (406) of AV signals;
- an output device (410) operable to:
 - o add an identifier to at least one of the AV signals;
 - o output the AV signals;
- a processor (414) operable to:
 - o instruct the output device to add the identifier in dependence on the first component being active.

- 17. (original) A component as claimed in claim 16 further comprising:
- a control interface (418) operable to send a relevant parameter associated with the identifier;
 and wherein the processor (414) is further operable to:
 - o instruct the control interface to send a relevant parameter associated with the identifier.
- 18. (currently amended) A second component (500) for use in the system of $\frac{1}{2}$ of claims 9 to $\frac{1}{2}$ comprising:
- a switching matrix (502) operable to:
 - o receive a plurality of signals;
 - o select at least one of the signals;
 - o output the at least one selected AV signals;
 - a store (510);
- a processor (512) operable to:
 - o analyse each signal of the plurality of received signals for the presence of an identifier;
 - o where an identifier is present, determine and store at least one parameter associated with the identifier;
 - o instruct the switching matrix to select a signal in dependence on the stored parameters.

- 19. (original) A component as claimed in claim 18 further comprising:
- a control interface (516) operable to receive a relevant parameter associated with the identifier;
 and wherein the processor (512) is further operable to:
 - o instruct the switching matrix to select a signal from the plurality of received signals on the basis of a comparison of the stored parameters and the relevant parameter.
- 20. (currently amended) A component as claimed in claim 16 or 17 and claim 18 or 19.
- 21. (currently amended) A component as claimed in any of elaims 17, 19 or 20 claim 17 wherein the control interface supports the Project50/CEC protocol.
- 22. (original) A component as claimed in claim 19, wherein the received signals are digital audio encoded using the SP/DIF protocol and the identifier is communicated using the user data bits of the SP/DIF protocol.
- 23. (currently amended) A record carrier comprising software operable to carry out the method of any of elaims 1 to 0 claim 1.

- 24. (currently amended) A software utility configured for carrying out the method steps as claimed in any of claims 1 to 8claim 1.
- 25. (original) A component including a processor, said processor being directed in its operations by a software utility as claimed in claim 24.